

KEP 980N



Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

| Product Description | Features |
|--|--|
| KEP980N is an oil extended EPDM rubber with narrow molecular weight distribution, high ethylene contents. It can be used to moldings in general, shock absorbing rubber, window seals and so on. | <ul style="list-style-type: none">- Good physical properties- High loadability- Superior processability- Good physical properties blending with SBR |

| Test items | Sale Specifications | Unit | Test Method |
|------------------------------------|---------------------|------|-----------------|
| Volatile Matter | Max 0.75 | wt % | ASTM D5668 |
| Mooney Viscosity ML(1+8)@125 °C | 58.0 ± 6.0 | MU | ASTM D1646 |
| Ethylene Contents | 70.5 ± 3.0 | wt % | ASTM D3900 |
| ENB Contents | 4.5 ± 1.0 | wt % | ASTM D6047 |
| Oil Contents | 75.0 ± 4.0 | phr | Internal Method |

Other Products Features

| | |
|---------------------|---|
| Product Form | Bale |
| Packaging | 25 kg/Bale in Carton/Mesh Box, LDPE film 750 kg(25 kg × 30) |
| Shelf Life | 24 months from date of production at room temperature in dry condition, exposure to light has to be avoided |
| The Others | RoHS Free |

Contact Information

| | |
|----------------------|--|
| Head Office | 8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000 |
| Plant | 613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822 |
| Revision Date | 06/01/2016 |
| Revision No. | 8 |