

Description Polyisoprene Rubber

Specification

PROPERTY	UNIT	LIMITS	TEST PROCEDURE
Volatile Matter	%	≤ 1.00	Zeon Standard Method
Ash	%	≤ 0.50	Zeon Standard Method
Mooney Viscosity {ML(1+4)100 °C}		74.0 - 90.0	Zeon Standard Method

- Shelf Life:** 3 years after date of manufacture in unopened original packaging .
Storage: Stored indoors in cool and dry conditions with no exposure to direct light.
Safety: Refer to the appropriate SDS for safety and handling.

**The specification may be changed
without any prior notification.**

ZEON

ZEON CORPORATION Division of Synthetic Rubber

6-2, Marunouchi, 1-Chome, Chiyoda-ku, Tokyo 100-8246 Tel:+81-3-3216-2337 Fax:+81-3-3216-0599

The information contained herein is believed to be reliable, but no presentations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained there from. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and product performance are the responsibility of the user. As the conditions or methods of use are beyond the control of Zeon Corporation, Zeon Corporation do not assume any responsibility and expressly disclaim any liability for any use of any material and the user assumes all risk and liability for any use or handling of any material. The seller makes no warranties, express or implied, including, but not limited to, the limited warranties or merchantability and fitness for a particular purpose. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to patented invention without permission of the patent owner.