

## Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP350 is an EPDM rubber with Medium molecular weight distribution, low ethylene, high ENB. It can be used to Cover strips, white sidewalls, window seals, gaskets, packing, and sponge.	<ul style="list-style-type: none"><li>- Medium Mooney viscosity with excellent Processability</li><li>- Ultra fast vulcanization speed.</li><li>- Suitable for blends with diene type rubbers</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	56.0 ± 6.0	MU	ASTM D1646
Ethylene Contents	56.5 ± 3.5	wt %	ASTM D3900
ENB Contents	7.9 ± 1.0	wt %	ASTM D6047

### Other Products Features

<b>Product Form</b>	Bale
<b>Packaging</b>	25 kg/Bag Mesh Box, LDPE film, 900 kg(25 kg × 36)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	12/02/2020
<b>Revision No.</b>	4